

KALTE THEKEN

COOLING DISPLAYS



Kühlung im Schalenbereich.
Cooling in the tub area.



Kühlvitrine Logic Cooling Display Logic

statische Kühlung +2° bis +6°C* im Schalenbereich • digitale Temperaturanzeige • Schiebetüren auf der Rückseite • langlebige LED-Beleuchtung für maximale Aufmerksamkeit • Absatzsteigerung durch optimale Sichtbarkeit der Produkte • besonders energieeffizient durch doppelte Verglasung • Scheiben aus gehärtetem Glas • äußerst kleiner Kompressor sorgt für wenig Platzbedarf • inkl. GN-Behälter

static cooling +2° up to +6°C* in the tub area • digital temperature display • sliding doors on the back • long-living LED lighting for maximal attention • increase your sales through ideal visibility of your products • particularly energy-efficient through double glazing • all glasses strengthened • little space requirement due to extra-small compressor unit • incl. GN containers



4x 1/3 GN x 40 mm
6x 1/3 GN x 40 mm



230 V / 161 W
230 V / 163 W



970 x 380 x 225 mm
1320 x 380 x 225 mm



27 kg *
32 kg *



05-70558
05-70559



1333,-*
1501,-*



Kühlung von oben und unten.
Top and bottom cooling.



Kühlvitrine Logic Sushi Cooling Display Logic Sushi

Kühlung von oben und unten • 0° bis +4°C* im gesamten Innenraum • digitale Temperaturanzeige • Schiebetüren auf der Rückseite • langlebige LED-Beleuchtung für maximale Aufmerksamkeit • Absatzsteigerung durch optimale Sichtbarkeit der Produkte • besonders energieeffizient durch doppelte Verglasung • Scheiben aus gehärtetem Glas • äußerst kleiner Kompressor sorgt für wenig Platzbedarf • inkl. GN-Behälter

top and bottom cooling • 0° up to +4°C* in the whole interior • digital temperature display • sliding doors on the back • long-living LED lighting for maximal attention • increase your sales through ideal visibility of your products • particularly energy-efficient through double glazing • all glasses strengthened • little space requirement due to extra-small compressor unit • incl. GN containers



6x 1/3 GN x 40 mm



230 V / 175 W



1320 x 380 x 300 mm



55 kg *



05-70560



2484,-*